

---

## **TP ATTACHMENT 2-4 – JOB VEHICLE SPECIFICATIONS**

### **Light-Duty Trucks**

Unless otherwise specified, furnish all units complete with standard equipment and factory-installed accessories as listed in the manufacturer's printed literature. The following items are minimum requirements specified herein, and provide whether shown as optional or standard equipment by the manufacturer. The following are some of those standard features or additional features as listed. Any additional requirements are reflected in the following the table for each vehicle. The additional requirements listed below any table are in lieu of, or in addition to, the following general requirements for light-duty trucks:

1. **Body:** 4X2 Pickup or Cab and Chassis.
  - a. **Pickup Bodies:** Straight / fleet side with steel cargo floors.
  - b. **Cab:** Conventional, Extended, or Crew.
2. **Air Bags: Required.** Manufacturer's standard to include side curtain/impact airbags if available from manufacturer (Exception: Units with 8,600 lb. GVWR and up.)
  - a. **Air Conditioning:** Required. Manufacturer's standard.
  - b. **AM/FM Radio:** Manufacturer's standard.
  - c. **Auxiliary Power Outlet:** One 12 volt.
  - d. **Seat, Cloth:** Front seats split bench 40/60, 40/20/40, or buckets. (Bench not acceptable)
  - e. **Jack, Handle, and Lug Wrench.**
  - f. **Power Package:** Includes power windows, power locks, power mirrors, cruise control, and tilt steering wheel. NOTE: Rearview Mirrors shall be the largest factory installed available.
  - g. **Sun Visors:** Dual.
  - h. **Window Tint:** OEM Standard Tint. Tinting shall meet California DMV regulations.
3. **Chassis:**
  - a. **Automatic Transmission:** Required
  - b. **Brakes:** ABS, required, manufacturer's standard; front disc, 2- or 4- wheel.
  - c. **Bumper (Full Width of Truck):** Installed front and rear-step bumper shall be manufacturer's standard.
  - d. **Spare Wheel and Tire:** OEM major Brand name for Full Size.
  - e. **Tires (including Spare):** Steel belted radial, all position, tubeless highway tread. Tires with raised white lettering are acceptable, if mounted with the black lettering facing away from vehicle.
  - f. **Electronic Stability Control:** If available (per FMVSS 126 all light duty vehicles (under GVWR 10,000) to have ESC installed by model year 2014)
4. **Cargo Weight:**
  - a. **Cargo Weight:** Deduct the cargo body weight from the body and payload allowance shown. The remainder is the cargo weight limit for the standard, base truck.
  - b. **Payload Allowance:** Weight of cargo that may be carried by the standard, base vehicle.
5. **Highway Work Zone**
  - a. **Light Bar (Yellow)**
  - b. **4 Corner Hide-a-way Strobes**
  - c. **Strobe Package in Headlights and tail lights**
  - d. **Back up alarm**
  - e. **2 Standard Traffic Cones**
6. **Safety Items**
  - a. **First Aid Kit**
  - b. **5 lb ABC Dry Chemical Fire Extinguisher with Bracket Mount**

**4X2 LIGHT DUTY TRUCK  
4X2 MID-SIZE CREW CAB PICKUP TRUCK  
SINGLE REAR WHEEL**

5/6-Cylinder, Short Bed 1/2 Ton 4 Full Door 843b - Mid-Size Crew Cab Pickup Truck, Single Rear Wheel, 5/6-Cylinder, Short Bed 1/2 Ton 4 Full Doors

---

<i><b>ITEM</b></i>	<i><b>Minimum Req.</b></i>
Wheelbase, inches	125
Approximate Payload Allowance, pounds	1,177
Length, Overall, inches	205
Length, Cargo, inches	50
GVWR, pounds	4900
Engines, Displacement, liters	3.7L 5 Cyl
Engines, Net HP	210
Engines, TORQUE	225
Transmission	4 speed auto

---

**Utility Vehicles (Carryalls, 2-Wheel Drive Utility, And Cargo Vans)**

Unless otherwise specified, furnish all units complete with standard equipment and factory-installed accessories as listed in the manufacturer's printed literature. The following items are minimum requirements specified herein, and provide whether shown as optional or standard equipment by the manufacturer. The following are some of those standard features or additional features as listed. Any additional requirements are provided in the following table for each series number. These additional requirements listed below any table are in lieu of, or in addition to, the following general requirements for utility vehicles:

1. **Body:**
  - a. **Air Bags:** Manufacturer's standard to include side curtain/impact airbags if available from manufacturer.
  - b. **Air Conditioning:** Manufacturer's standard.
  - c. **Arm Rests:** Left door only. Both right and left arm rests are required if right front seat is provided.
  - d. **AM/FM Radio:** Manufacturer's standard.
  - e. **Auxiliary Power Outlet:** 12 volt.
  - f. **Heater and Defroster:** See Accessory Specifications.
  - g. **Power Package:** Includes power windows, power locks, power mirrors, cruise control, and tilt steering wheel.
  - h. **Seat, Cloth:** Front seats split bench 40/60, 40/20/40, or buckets. (Bench not acceptable)
  - i. **Sun Visor:** Driver's side only. Dual sun visors are required if right front seat is provided.
  - j. **Windshield Wipers:** Dual electric 2-speed type with intermittent feature windshield washers.
  - k. **Window Tint:** OEM Standard Tint. Tinting shall meet California DMV regulations.
2. **Chassis:**
  - a. **Power Brakes, ABS, required:** Manufacturer's standard; front disc, 2- or 4-wheel.
  - b. **Automatic Transmission**
  - c. **Bumpers:** Manufacturer's standard front and rear bumper.
  - d. **Ground Ratings:** As required for the GVWR certified.
  - e. **Jack, Handle, and Lug Wrench**
  - f. **Shock Absorbers:** Front and rear. Manufacturer's heaviest duty shocks without increase in vehicle trim level.
  - g. **Spare Wheel and Tire (mounted on carrier):** Manufacturer's standard. Must be OEM brand name, type and size of tire to those on the vehicle.
  - h. **Tires (including spare):** Steel belted radial type tubeless tires.
  - i. **Electronic Stability Control:** If available (per FMVSS 126 all light duty vehicles (under GVWR 10,000) to have ESC installed by model year 2014)
  - j. **Power Steering:** Manufacturer's standard
  - k. **Flex Fuel,** if available
3. **Cargo Weight:**
  - a. **Approximate Payload Allowance:** Weight of cargo that may be carried by the standard, base vehicle
4. **Highway Work Zone**
  - a. **Light Bar (Yellow)**
  - b. **4 Corner Hide-a-way Strobes**
  - c. **Strobe Package in Headlights and tail lights**
  - d. **Back up alarm**
  - e. **2 Standard Traffic Cones**

**5. Safety Items**

- a. **First Aid Kit**
- b. **5 lb ABC Dry Chemical Fire Extinguisher with Bracket Mount**

**UTILITY VEHICLE  
SMALL SIZE**

6-Cylinder, Light-Duty, 4-Door, 2-Wheel Drive 661b - Utility Vehicle, Small Size, 6-Cyl, 4-Door, Light-Duty, Rwd

<i>ITEM</i>	<i>Minimum Req.</i>
Wheelbase, inches	103
Approximate Payload Allowance, pounds	1,099
Length, Overall, inches	174.7
Length, Cargo, inches	61.5
GVWR, pounds	4,520
Engines, Displacement, liters	3.0L V6
Engines, Net HP	190
Engines, TORQUE	193
Transmission	Auto 4-Speed